


Disable a specific IP address from accessing the switch



AI Overview

You can disable an IP address on a switch by either removing the IP from the VLAN interface or administratively disabling Layer 3 routing on the VLAN. Removing or Disabling the IP Address Using CLI to Remove IP from VLAN Interface On many managed switches, you can remove the IP address assigned to a VLAN interface. For example, on a Cisco or Cambium switch: Enter global configuration mode: configure terminal Select the VLAN interface: interface vlan 1 Remove the IP address: no ip address Exit configuration mode: end This effectively disables the switch's IP for management or routing purposes while keeping the VLAN active for Layer 2 switching. Disabling Layer 3 Routing on VLANs Some switches, like Aruba or HPE models, allow you to administratively disable IP functionality without removing the Layer 3 configuration: Use the command or management interface to toggle Layer 3 routing inactive on the VLAN. The switch continues Layer 2 switching but will not respond to IP traffic on that VLAN until re-enabled. Removing Default Gateway (Optional) If the switch has a default gateway configured, you can remove it to prevent routing to external networks: Enter global configuration mode: configure terminal Remove the default gateway: no ip default-gateway [gateway-ip] This ensures the switch does not forward traffic outside its local subnet. Additional Considerations DHCP-Assigned IPs: If the switch is using DHCP, disable it first with no ip address dhcp before assigning or removing a static IP. Backup VLANs: Disabling IP on a VLAN can be useful for backup configurations, allowing quick reactivation of Layer 3 routing when needed. Saving Configuration: After making changes, save the configuration to ensure the IP remains disabled after a reboot, typically with write memory or copy running-config startup-config. By following these steps, you can effectively disable the IP address on a switch...

Article Content

Connecting Azure Sphere to Azure IoT Edge | Microsoft Community Hub

The starting point for the lab is: Azure Sphere Device is claimed to tenant Device is in developer mode Device is connected to Wi-Fi IoT Edge IoT Edge runtime is installed and IoT edge

How to block one subnet for accessing internet through access list ...

Hello, I would like to know how to block one subnet for accessing internet through access list in cisco layer 3 switch. I have one cisco layer 3 switch and there are 5 vlans and SVIs have been

How do I use access control to allow or block devices from accessing ...

Before a device accesses your router's or Orbi's Internet connection, you must enter its MAC address for an Ethernet connection and its MAC address for a WiFi connection in the allowed

Localhost Refused to Connect Error: 5 Confirmed Ways

When you try to connect to an IP address, you usually try to connect to a different computer. However, since localhost uses the loopback address

How to configure Access Control to block users' access to the switch ...

You can configure Access Control to allow only specific users to access the switch and block the others. Access Control can work in three modes: IP-based Mode, MAC-based Mode and

Controlling Internet Access with OpenWRT Firewall: Blocking

Learn how to control internet access for devices on your network using OpenWRT's firewall capabilities, including blocking specific websites, managing access to NAS resources, and

How to Block Unwanted WAN IP Address from Your

This post provides a configuration guide to block unwanted public IP addresses from accessing your WAN or services. In another use case, you might

Blocking single device by IP access to Internet

I want to block one device, by IP, on my LAN, from accessing the Internet. I've tried a floating rule that blocks the IP as source, direction out, and I have tried a similar rule on the WAN

Create Availability Group Listener Fails with Message 19471, "The

In the Roles pane, right-click the availability group resource and choose Add Resource and then Client Access Point. Enter a DNS Name and click in the affirmative through the rest of the

Welcome | Vector

Putting Engineers in the Fast Lane Development tools, software, hardware and ingenious solutions to simplify the development of embedded systems.

Solved: Access list to restrict certain IPs

Allow all machines that has a valid IP i.e any IP from 192.168.1.101 to 192.168.1.150 to connect to the cisco router and consequently access the Internet. Thus a machine with an IP such a

How Do I iptables Block Incoming IP Addresses?

Learn how to use the iptables command to block incoming traffic from specific IP (IPv4 or IPv6) addresses using the CLI on Linux system.

Advanced settings configuration in WSL | Microsoft Learn

A guide to the wsl nf and .wslconfig files used for configuring settings when running multiple Linux distributions on Windows Subsystem for Linux.

How can I block an IP address using access rules?

This is a scenario based article where we will be blocking an IP address from accessing the WAN. Let us consider a computer on the LAN

Introducing Exchange Online Tenant Outbound Email

We're introducing new tenant-level outbound email limits (also known as the Tenant External Recipient Rate Limit or TERRL).

Manage runners | GitLab Docs

Determine the IP address of an instance runner Prerequisites: You must have administrator access to the instance. To determine the IP address of an instance runner: In the upper-right corner, select

Block IP Addresses: Methods and Best Practices

Blocking an IP address is one of the most effective ways to control traffic and protect systems from malicious or unauthorized connections. This text will explain why IP blocking is useful,

Catalyst 2960 and 2960-S Software Configuration Guide, 12.2 (55)SE

Storm control (or traffic suppression) monitors packets passing from an interface to the switching bus and determines if the packet is unicast, multicast, or broadcast. The switch counts the

MicroSIP Documentation

Public IP will be used in later SIP queries in Via, Contact and SDP. See also: Public address, STUN. Disable Session Timers Specify the usage of Session Timers.

Changes with Storage on Cloud and Storage Classification in VMM

First published on TECHNET on May 19, 2014 Storage Classification was introduced in System Center 2012 Virtual Machine Manager (VMM 2012) to provide the...

Default Outbound Access in Azure

How and when default outbound access is provided If a Virtual Machine (VM) is deployed without an explicit outbound connectivity method,

Android Debug Bridge (adb) | Android Studio | Android

Android Debug Bridge (adb) is a versatile command-line tool that lets you communicate with a device. The adb command facilitates a variety of device

Azure OpenAI Service Multitenant Load Balancing and

To distribute calls efficiently, the service leverages a round-robin scheduling algorithm or maps requests to specific Azure OpenAI Service

How to Login with a Local Account instead of Domain

Learn how to log on to Windows with a local account instead of a domain account. Step-by-step guide with tips for Group Policy, RDP, and DCs.

UniFi Gateway

UniFi Gateway - Port Forwarding Port Forwarding allows external devices or services to access specific resources within your UniFi network—such as a web

Configure network security for Azure Key Vault | Microsoft Learn

Select the resource (specific instance of the service). Select the Properties blade under Settings. Look for the IP Address field. Copy this value or range and enter it into the key vault firewall

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.sphplantsales.co.za>

Email: info@sphplantsales.co.za

Phone: +27 64 827 3915

Address: Unit 9, Highveld Technopark, 43 Atlas Road, Johannesburg, 2196,
South Africa

This document is for informational purposes only. Specifications subject to
change without notice.

